

Model Number 3741F122G		DC RESPONSE ACCELEROMETER			Revision: B ECN #: 53791	
Performance		ENGLISH		SI	OPTIONAL VERSIONS	
Sensitivity(± 3 %)		1,350 mV/g		137.6 mV/(m/s ²)	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Measurement Range		± 2 g pk		± 19.6 m/s ² pk		
Frequency Range(± 5 %)		0 to 250 Hz		0 to 250 Hz		
Frequency Range(± 10 %)		0 to 350 Hz		0 to 350 Hz		
Resonant Frequency		1.2 kHz		1.2 kHz		
Phase Response(10 Hz)		< 2.5 °		< 2.5 °		
Non-Linearity(Typical)		0.3 %		0.3 %		
Non-Linearity(Max)		1 %		1 %		
Broadband Resolution(0.5 to 100 Hz)		0.06 mg rms		0.0006 m/s ² rms		
Transverse Sensitivity(Typical)		1 %		1 %		
Transverse Sensitivity(Max)		3 %		3 %		
Environmental						
Overload Limit(Shock)		± 5,000 g pk		± 49,050 m/s ² pk		
Temperature Range(Operating)		-65 to 250 °F		-54.0 to 121 °C		
Temperature Range(Storage)		-65 to 250 °F		-54.0 to 121 °C		
Temperature Coefficient of Sensitivity		± 1 %		± 1 %	[4][2]	
Zero g Offset Temperature Coefficient		± 1 % FSO		± 1 % FSO	[5][4][2]	
Base Strain Sensitivity		.001 g/με		.01 (m/s ²)/με	[2]	
Magnetic Sensitivity		40 μg/gauss		3.9 (m/s ²)/Tesla	[2]	
Electrical						
Excitation Voltage		5 to 32 VDC		5 to 32 VDC		
Current Consumption		≤ 5 mA		≤ 5 mA		
Output Impedance		≤ 120 Ohm		≤ 120 Ohm		
Offset Voltage(0 g)		± 20 mVDC		± 20 mVDC	[6]	
Common Mode Voltage(± 0.1 VDC)		+ 1.65 VDC		+ 1.65 VDC		
Spectral Noise(1 Hz)		6 μg/√Hz		59 (μm/s ²)/√Hz	[2]	
Spectral Noise(10 Hz)		6 μg/√Hz		59 (μm/s ²)/√Hz	[2]	
Spectral Noise(100 Hz)		6 μg/√Hz		59 (μm/s ²)/√Hz	[2]	
Electrical Isolation(Case)		> 10 ⁸ Ohm		> 10 ⁸ Ohm	[7]	
Physical						
Housing Material		Anodized Aluminum		Anodized Aluminum		
Sealing		Epoxy		Epoxy		
Size (Height x Length x Width)		0.30 in x 1.00 in x .85 in		7.62 mm x 25.4 mm x 21.6 mm		
Weight(without cable)		0.35 oz		9.92 gm	[2]	
Electrical Connector		Integral Cable		Integral Cable		
Electrical Connection Position		Side		Side		
Cable Termination		Pigtail Ends		Pigtail Ends		
Cable Type		010 4-cond Shielded		010 4-cond Shielded		
Cable Length		10 ft		3 m		
Mounting		Through Holes (2)		Through Holes (2)		
CEUKCA^[8] All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.						
Entered: NDEngineer: NJFSales: JMApproved: BAMSpec Number: Date: 05/08/2023Date: 05/08/2023Date: 05/08/2023Date: 05/08/202369810 PCB PIEZOTRONICS AN AMPHENOL COMPANY Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043						

Model Number 3741F125G	DC RESPONSE ACCELEROMETER			Revision: NR ECN #: 55613
Performance		ENGLISH	SI	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Sensitivity(± 3 %)		540 mV/g	55.0 mV/(m/s ²) [1]	
Measurement Range		± 5 g pk	± 49.0 m/s ² pk	
Frequency Range(± 5 %)		0 to 700 Hz	0 to 700 Hz	
Frequency Range(± 10 %)		0 to 1,000 Hz	0 to 1,000 Hz	
Resonant Frequency		1.9 kHz	1.9 kHz [2]	
Phase Response(100 Hz)		< 10 °	< 10 °	
Non- Linearity(Typical)		0.3 %	0.3 % [3]	
Non- Linearity(Max)		1 %	1 % [3]	
Broadband Resolution(0.5 to 100 Hz)		0.15 mg rms	0.0015 m/s ² rms [2]	
Transverse Sensitivity(Typical)		1 %	1 %	
Transverse Sensitivity(Max)		3 %	3 %	
Environmental				
Overload Limit(Shock)		± 5,000 g pk	± 49,050 m/s ² pk	
Temperature Range(Operating)		-65 to 250 °F	-54.0 to 121 °C	
Temperature Range(Storage)		-65 to 250 °F	-54.0 to 121 °C	
Temperature Coefficient of Sensitivity		± 1 %	± 1 % [4][2]	
Zero g Offset Temperature Coefficient		± 1 % FSO	± 1 % FSO [5][4][2]	
Base Strain Sensitivity		.001 g/με	.01 (m/s ²)/με [2]	
Magnetic Sensitivity		40 μg/gauss	3.9 (m/s ²)/Tesla [2]	
Electrical				
Excitation Voltage		5 to 32 VDC	5 to 32 VDC	
Current Consumption		≤ 5 mA	≤ 5 mA	
Output Impedance		≤ 120 Ohm	≤ 120 Ohm	
Offset Voltage(0 g)		± 20 mVDC	± 20 mVDC [6]	
Common Mode Voltage(± 0.1 VDC)		+ 1.65 VDC	+ 1.65 VDC	
Spectral Noise(1 Hz)		15 μg/√Hz	147 (μm/s ²)/√Hz [2]	
Spectral Noise(10 Hz)		15 μg/√Hz	147 (μm/s ²)/√Hz [2]	
Spectral Noise(100 Hz)		15 μg/√Hz	147 (μm/s ²)/√Hz [2]	
Electrical Isolation(Case)		> 10 ⁸ Ohm	> 10 ⁸ Ohm [7]	
Physical				
Housing Material		Anodized Aluminum	Anodized Aluminum	
Sealing		Epoxy	Epoxy	
Size (Height x Length x Width)		0.30 in x 1.00 in x .85 in	7.62 mm x 25.4 mm x 21.6 mm	
Weight(without cable)		0.35 oz	9.92 gm [2]	
Electrical Connector		Integral Cable	Integral Cable	
Electrical Connection Position		Side	Side	
Cable Termination		Pigtail Ends	Pigtail Ends	
Cable Type		010 4-cond Shielded	010 4-cond Shielded	
Cable Length		10 ft	3 m	
Mounting		Through Holes (2)	Through Holes (2)	
NOTES: [1] Measured at 100 Hz, 1 grms. [2] Typical. [3] Zero-based, least-squares, straight line method. [4] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C) [5] FSO= Full Scale Output over the Measurement Range [6] Offset tolerance is based on manufacturers supplied cable length. [7] Case and shield to mounting surface or cable leads. [8] See PCB Declaration of Conformance PS027 for details.				
SUPPLIED ACCESSORIES: Model 081A103 Mounting screw (2) Model ACS-172 Phase and Amplitude Calibration from 5 Hz to +5% frequency range (1) Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)				
OPTIONAL ACCESSORIES: Model 080A208 Triaxial mounting block				
Entered: ND	Engineer: NJF	Sales: JM	Approved: NJF	Spec Number:
Date: 03/31/2025	Date: 03/31/2025	Date: 03/31/2025	Date: 03/31/2025	79772
  Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com				
3425 Walden Avenue, Depew, NY 14043				

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
This model, designated with an RH prefix, is RoHS compliant. For further details, and to obtain PCB's RoHS Statement of Conformance, please visit <http://www.pcb.com>

Model Number 3741F1210G		DC RESPONSE ACCELEROMETER		Revision: B ECN #: 53791	
Performance		ENGLISH		SI	
Sensitivity(± 3 %)		270 mV/g		27.5 mV/(m/s ²) [1]	
Measurement Range		± 10 g pk		± 98.1 m/s ² pk	
Frequency Range(± 5 %)		0 to 1,000 Hz		0 to 1,000 Hz	
Frequency Range(± 10 %)		0 to 1,500 Hz		0 to 1,500 Hz	
Resonant Frequency		3.2 kHz		3.2 kHz [2]	
Phase Response(100 Hz)		< 10 °		< 10 °	
Non-Linearity(Typical)		0.3 %		0.3 % [3]	
Non-Linearity(Max)		1 %		1 % [3]	
Broadband Resolution(0.5 to 100 Hz)		0.3 mg rms		0.003 m/s ² rms [2]	
Transverse Sensitivity(Typical)		1 %		1 %	
Transverse Sensitivity(Max)		3 %		3 %	
Environmental					
Overload Limit(Shock)		± 5,000 g pk		± 49,050 m/s ² pk	
Temperature Range(Operating)		-65 to 250 °F		-54.0 to 121 °C	
Temperature Range(Storage)		-65 to 250 °F		-54.0 to 121 °C	
Temperature Coefficient of Sensitivity		± 1 %		± 1 % [2][4]	
Zero g Offset Temperature Coefficient		± 1 % FSO		± 1 % FSO [5][4][2]	
Base Strain Sensitivity		.001 g/με		.01 (m/s ²)/με [2]	
Magnetic Sensitivity		40 μg/gauss		3.9 (m/s ²)/Tesla [2]	
Electrical					
Excitation Voltage		5 to 32 VDC		5 to 32 VDC	
Current Consumption		≤ 5 mA		≤ 5 mA	
Output Impedance		≤ 120 Ohm		≤ 120 Ohm	
Offset Voltage(0 g)		± 20 mVDC		± 20 mVDC [6]	
Common Mode Voltage(± 0.1 VDC)		+ 1.65 VDC		+ 1.65 VDC	
Spectral Noise(1 Hz)		30 μg/√Hz		294 (μm/s ²)/√Hz [2]	
Spectral Noise(10 Hz)		30 μg/√Hz		294 (μm/s ²)/√Hz [2]	
Spectral Noise(100 Hz)		30 μg/√Hz		294 (μm/s ²)/√Hz [2]	
Electrical Isolation(Case)		> 10 ⁸ Ohm		> 10 ⁸ Ohm [7]	
Physical					
Housing Material		Anodized Aluminum		Anodized Aluminum	
Sealing		Epoxy		Epoxy	
Size (Height x Length x Width)		0.30 in x 1.00 in x .85 in		7.62 mm x 25.4 mm x 21.6 mm	
Weight(without cable)		0.35 oz		9.92 gm [2]	
Electrical Connector		Integral Cable		Integral Cable	
Electrical Connection Position		Side		Side	
Cable Termination		Pigtail Ends		Pigtail Ends	
Cable Type		010 4-cond Shielded		010 4-cond Shielded	
Cable Length		10 ft		3 m	
Mounting		Through Holes (2)		Through Holes (2)	
OPTIONAL VERSIONS					
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.					
NOTES:					
[1]Measured at 100 Hz, 1 grms.					
[2]Typical.					
[3]Zero-based, least-squares, straight line method.					
[4]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)					
[5]FSO= Full Scale Output over the Measurement Range					
[6]Offset tolerance is based on manufacturers supplied cable length.					
[7]Case and shield to mounting surface or cable leads.					
[8]See PCB Declaration of Conformance PS027 for details.					
SUPPLIED ACCESSORIES:					
Model 081A103 Mounting screw (2)					
Model ACS-172 Phase and Amplitude Calibration from 5 Hz to +5% frequency range (1)					
Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)					
OPTIONAL ACCESSORIES:					
Model 080A208 Triaxial mounting block					
Entered: ND		Engineer: NJF		Sales: JM	
Approved: BAM		Spec Number:			
Date: 05/05/2023		Date: 05/05/2023		Date: 05/05/2023	
Date: 05/05/2023		Date: 05/05/2023		69811	
					
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.					
 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com					
3425 Walden Avenue, Depew, NY 14043					

CE
UK
CA^[8]

Model Number 3741F1250G	DC RESPONSE ACCELEROMETER			Revision: B ECN #: 53791										
Performance		ENGLISH	SI	OPTIONAL VERSIONS										
Sensitivity(± 3 %)		54 mV/g	5.5 mV/(m/s ²)	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.										
Measurement Range		± 50 g pk	± 490.3 m/s ² pk											
Frequency Range(± 5 %)		0 to 1,500 Hz	0 to 1,500 Hz											
Frequency Range(± 10 %)		0 to 2,000 Hz	0 to 2,000 Hz											
Resonant Frequency		6.5 kHz	6.5 kHz											
Phase Response(100 Hz)		< 10 °	< 10 °											
Non-Linearity(Typical)		0.3 %	0.3 %											
Non-Linearity(Max)		1 %	1 %											
Broadband Resolution(0.5 to 100 Hz)		1.5 mg rms	0.015 m/s ² rms											
Transverse Sensitivity(Typical)		1 %	1 %											
Transverse Sensitivity(Max)		3 %	3 %											
Environmental														
Overload Limit(Shock)		± 5,000 g pk	± 49,050 m/s ² pk											
Temperature Range(Operating)		-65 to 250 °F	-54.0 to 121 °C											
Temperature Range(Storage)		-65 to 250 °F	-54.0 to 121 °C											
Temperature Coefficient of Sensitivity		± 1 %	± 1 %	[2][4]										
Zero g Offset Temperature Coefficient		± 1 % FSO	± 1 % FSO	[5][4][2]										
Base Strain Sensitivity		.001 g/με	.01 (m/s ²)/με	[2]										
Magnetic Sensitivity		40 μg/gauss	3.9 (m/s ²)/Tesla	[2]										
Electrical														
Excitation Voltage		5 to 32 VDC	5 to 32 VDC											
Current Consumption		≤ 5 mA	≤ 5 mA											
Output Impedance		≤ 120 Ohm	≤ 120 Ohm											
Offset Voltage(0 g)		± 20 mVDC	± 20 mVDC	[6]										
Common Mode Voltage(± 0.1 VDC)		+ 1.65 VDC	+ 1.65 VDC											
Spectral Noise(1 Hz)		150 μg/√Hz	1,472 (μm/s ²)/√Hz	[2]										
Spectral Noise(10 Hz)		150 μg/√Hz	1,472 (μm/s ²)/√Hz	[2]										
Spectral Noise(100 Hz)		150 μg/√Hz	1,472 (μm/s ²)/√Hz	[2]										
Electrical Isolation(Case)		> 10 ⁸ Ohm	> 10 ⁸ Ohm	[7]										
Physical														
Housing Material		Anodized Aluminum	Anodized Aluminum											
Sealing		Epoxy	Epoxy											
Size (Height x Length x Width)		0.30 in x 1.00 in x .85 in	7.62 mm x 25.4 mm x 21.6 mm											
Weight(without cable)		0.35 oz	9.92 gm	[2]										
Electrical Connector		Integral Cable	Integral Cable											
Electrical Connection Position		Side	Side											
Cable Termination		Pigtail Ends	Pigtail Ends											
Cable Type		010 4-cond Shielded	010 4-cond Shielded											
Cable Length		10 ft	3 m											
Mounting		Through Holes (2)	Through Holes (2)											
NOTES:														
[1]Measured at 100 Hz, 10 grms.														
[2]Typical.														
[3]Zero-based, least-squares, straight line method.														
[4]-65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)														
[5]FSO = Full Scale Output over the Measurement Range (4VDC).														
[6]Offset tolerance is based on manufacturers supplied cable length.														
[7]Case and shield to mounting surface or cable leads.														
[8]See PCB Declaration of Conformance PS027 for details.														
SUPPLIED ACCESSORIES:														
Model 081A103 Mounting screw (2)														
Model ACS-103 Phase and Amplitude Calibration from 2 Hz to +5% of frequency range (1)														
Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2)														
OPTIONAL ACCESSORIES:														
Model 080A208 Triaxial mounting block														
<table><tr><td>Entered: ND</td><td>Engineer: NJF</td><td>Sales: JM</td><td>Approved: BAM</td><td>Spec Number:</td></tr><tr><td>Date: 05/08/2023</td><td>Date: 05/08/2023</td><td>Date: 05/08/2023</td><td>Date: 05/08/2023</td><td>69813</td></tr></table>					Entered: ND	Engineer: NJF	Sales: JM	Approved: BAM	Spec Number:	Date: 05/08/2023	Date: 05/08/2023	Date: 05/08/2023	Date: 05/08/2023	69813
Entered: ND	Engineer: NJF	Sales: JM	Approved: BAM	Spec Number:										
Date: 05/08/2023	Date: 05/08/2023	Date: 05/08/2023	Date: 05/08/2023	69813										
 PCB PIEZOTRONICS AN AMPHENOL COMPANY Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043														
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.														

Model Number 3741F12200G		DC RESPONSE ACCELEROMETER			Revision: B ECN #: 53791										
Performance		ENGLISH	SI	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.											
Sensitivity(± 3 %)	13.5 mV/g	1.38 mV/(m/s ²)	[1]												
Measurement Range	± 200 g pk	± 1961.3 m/s ² pk													
Frequency Range(± 5 %)	0 to 1,500 Hz	0 to 1,500 Hz													
Frequency Range(± 10 %)	0 to 2,500 Hz	0 to 2,500 Hz													
Resonant Frequency	11.8 kHz	11.8 kHz	[2]												
Phase Response(100 Hz)	< 10 °	< 10 °													
Non-Linearity(Typical)	0.3 %	0.3 %	[3]												
Non-Linearity(Max)	1 %	1 %	[3]												
Broadband Resolution(0.5 to 100 Hz)	6 mg rms	0.06 m/s ² rms	[2]												
Transverse Sensitivity(Typical)	1 %	1 %													
Transverse Sensitivity(Max)	3 %	3 %													
Environmental															
Overload Limit(Shock)	± 5,000 g pk	± 49,050 m/s ² pk													
Temperature Range(Operating)	-65 to 250 °F	50 to 121 °C													
Temperature Range(Storage)	-65 to 250 °F	-54.0 to 121 °C													
Temperature Coefficient of Sensitivity	± 1 %	± 1 %	[4][2]												
Zero g Offset Temperature Coefficient	± 1 % FSO	± 1 % FSO	[5][4][2]												
Base Strain Sensitivity	.001 g/με	0.01 (m/s ²)/με	[2]												
Magnetic Sensitivity	40 μg/gauss	3.9 (m/s ²)/Tesla	[2]												
Electrical															
Excitation Voltage	5 to 32 VDC	5 to 32 VDC													
Current Consumption	≤ 5 mA	≤ 5 mA													
Output Impedance	≤ 120 Ohm	≤ 120 Ohm													
Offset Voltage(0 g)	± 20 mVDC	± 20 mVDC	[6]												
Common Mode Voltage(± 0.1 VDC)	+ 1.65 VDC	+ 1.65 VDC													
Spectral Noise(1 Hz)	600 μg/√Hz	5,886 (μm/s ²)/√Hz	[2]												
Spectral Noise(10 Hz)	600 μg/√Hz	5,886 (μm/s ²)/√Hz	[2]												
Spectral Noise(100 Hz)	600 μg/√Hz	5,886 (μm/s ²)/√Hz	[2]												
Electrical Isolation(Case)	> 10 ⁸ Ohm	> 10 ⁸ Ohm	[7]												
Physical				NOTES: [1] Measured at 100 Hz, 10 grms. [2] Typical. [3] Zero-based, least-squares, straight line method. [4] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C) [5] FSO= Full Scale Output over the Measurement Range [6] Offset tolerance is based on manufacturers supplied cable length. [7] Case and shield to mounting surface or cable leads. [8] See PCB Declaration of Conformance PS027 for details.											
Housing Material	Anodized Aluminum	Anodized Aluminum													
Sealing	Epoxy	Epoxy													
Size (Height x Length x Width)	0.30 in x 1.00 in x .85 in	7.62 mm x 25.4 mm x 21.6 mm													
Weight(without cable)	0.35 oz	9.92 gm	[2]												
Electrical Connector	Integral Cable	Integral Cable													
Electrical Connection Position	Side	Side													
Cable Termination	Pigtail Ends	Pigtail Ends													
Cable Type	010 4-cond Shielded	010 4-cond Shielded													
Cable Length	10 ft	10 ft													
Mounting	Through Holes (2)	Through Holes (2)													
				SUPPLIED ACCESSORIES: Model 081A103 Mounting screw (2) Model ACS-172 Phase and Amplitude Calibration from 5 Hz to +5% frequency range (1) Model M081A103 Mounting screw and washer, M3 x 0.5 thread (2) OPTIONAL ACCESSORIES: Model 080A208 Triaxial mounting block											
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				<table> <tr> <td>Entered: ND</td><td>Engineer: NJF</td><td>Sales: JM</td><td>Approved: BAM</td><td>Spec Number:</td></tr> <tr> <td>Date: 05/10/2023</td><td>Date: 05/10/2023</td><td>Date: 05/10/2023</td><td>Date: 05/10/2023</td><td>69815</td></tr> </table>		Entered: ND	Engineer: NJF	Sales: JM	Approved: BAM	Spec Number:	Date: 05/10/2023	Date: 05/10/2023	Date: 05/10/2023	Date: 05/10/2023	69815
Entered: ND	Engineer: NJF	Sales: JM	Approved: BAM	Spec Number:											
Date: 05/10/2023	Date: 05/10/2023	Date: 05/10/2023	Date: 05/10/2023	69815											
				Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com											
3425 Walden Avenue, Depew, NY 14043															